Subject Index for
Heat Transfer—Japanese Research, Volume 22, 1993

Absorption enhancement: **4**: 355–371
Acoustic streaming: **6**: 546–558
Active thermal insulation: **3**: 224–237
Adsorption-type chiller: **7**: 703–715
Aiding flow: **3**: 213–223
Algebraic stress model: **2**: 120–138
Analysis: **7**: 731–746
Anisotropic porous matrix: **2**: 139–153
Annular two-phase flow: **5**: 447–461
Axial laminar flow: **2**: 198–212
Axisymmetric flow: **5**: 493–505

Boiler: **2**: 107–119
Boiling: **3**: 281–293; **6**: 611–624; **7**: 643–660; **8**: 812–827
Boiling heat transfer in narrow places: **7**: 703–715
Boiling heat-transfer promotion: **7**: 703–715
Boiling heat transfer under reduced pressures: **7**: 703–715
Boundary-fitted coordinate systems: **2**: 120–138
Boundary layer: **5**: 506–517
Buoyant plume: **2**: 107–119

Carbon brick: **8**: 780–795
Carbon content: **3**: 294–304
Carbon electrode: **8**: 780–795
Carbonization: **5**: 435–446
Cavitation: **6**: 546–558
Cavity: **6**: 531–545
Circular cylinder: **5**: 506–517; **7**: 690–702
Circular tube flows: **2**: 154–170
Circulating fluidized bed: **3**: 269–280
Circulation mass velocity: **8**: 812–827
Circumferential distribution: **5**: 447–461
Coalesced bubble-emission frequency: **7**: 703–715
Colloidal solution: **7**: 643–660
Combined convection: **2**: 198–212; **3**: 213–223
Composites: **8**: 780–795
Computational fluid dynamics: **4**: 325–339
Concentration distribution: **1**: 28–47
Concentration measurement: **1**: 14–27
Concentration: **1**: 48–65
Condensation: **4**: 372–386
Condenser: **4**: 372–386
Conduction cooling: **1**: 78–89; **1**: 90–106
Constant magnetic field: **7**: 672–689
Contact resistance: **1**: 90–106
Convective heat transfer: **2**: 154–170
Cooling: **6**: 625–641
Cooling curve: **3**: 294–304
Critical heat flux: **6**: 611–624; **8**: 812–827
Cross flow: **7**: 690–702
Cryogenics: **8**: 747–762
Cylinder: **2**: 198–212
Czochralski process: **4**: 416–434

Delay time: **5**: 480–492
Density inversion: **6**: 596–610
Dissimilar gas: **1**: 14–27; **1**: 28–47
Distorting duct: **2**: 120–138
Double tube: **8**: 812–827
Double-diffusive layer: **3**: 250–268
Double-pulsed ruby laser: **4**: 355–371
Double-tube annular flow: **7**: 661–671

Eddy: **8**: 796–811
Effective thermal conductivity: **6**: 573–594
Electrochemical method: **2**: 184–197
Electromagnetic ultrasonic technique: **8**: 780–795
Electronic component: **1**: 78–89; **1**: 90–106
Energy storage: **8**: 763–779
Experimental data: **2**: 198–212
Extended heat-transfer surface: **1**: 78–89; **1**: 90–106; **4**: 372–386

Falling film: **4**: 355–371
Fast fluidized bed: **3**: 269–280

Film condensation: 1: 66–77
Film inversion: 5: 447–461
Film thickness: 5: 447–461
Finite-size horizontal plate: 1: 66–77
Fins: 4: 398–415
Flow measurement: 1: 14–27; 1: 28–47; 1: 48–65;
Flow visualization: 8: 828–837
Forced convection: 1: 1–13; 3: 213–223; 3: 238–249; 4: 325–339; 5: 506–517; 7: 661–671; 7: 690–702; 8: 828–837
Forced-convection heat transfer: 6: 573–594
Free stream turbulence: 1: 1–13
Freezing: 7: 731–746

Gas solid contactor: 3: 269–280
Geothermal energy: 4: 340–354
Geothermal-energy boiling: 7: 661–671
Graphite: 5: 435–446
Green carbon: 5: 435–446
Greenhouse growing system design: 4: 340–354
Greenhouse growing system development: 4: 340–354
Ground-source heat pump: 7: 661–671

HCFC-22: 7: 661–671
Heat conduction: 1: 78–89; 1: 90–106; 4: 416–434; 6: 531–545; 7: 731–746
Heat exchanger: 7: 690–702
Heat loss in energy transport: 3: 305–324
Heat pipe: 6: 611–624
Heat pump: 7: 661–671
Heat transfer: 1: 1–13; 1: 66–77; 1: 78–89; 1: 90–106; 2: 107–119; 2: 139–153; 2: 171–183; 2: 184–197; 2: 198–212; 3: 213–223; 3: 238–249; 3: 269–280; 3: 281–293; 4: 398–415; 4: 416–434; 5: 462–479; 5: 493–505; 5: 518–530; 6: 531–545; 6: 559–572; 6: 596–610; 6: 625–641; 7: 643–660; 7: 661–671; 7: 690–702; 7: 716–730; 8: 747–762; 8: 796–811; 8: 812–827; 8: 828–837; 8: 838–848
Heat-transfer coefficient: 2: 171–183; 3: 269–280; 8: 838–848
Heat-transfer control: 3: 224–237
Heat-transfer enhancement: 2: 184–197; 3: 238–249; 4: 372–386; 4: 387–397; 5: 480–492; 5: 506–517; 6: 546–558; 7: 643–660; 7: 716–730; 7: 731–746; 8: 796–811
Hele-Shaw flow: 5: 531–545
Helically coiled tube: 5: 447–461
High heat flux: 2: 154–170
Honeycomb: 2: 107–119
Horizontal fluid layer: 2: 107–119
Horizontal low-finned tube: 4: 372–386
Hot wire: 1: 14–27; 1: 28–47; 1: 48–65
Hot-wire method: 5: 435–446

Inclined plates: 3: 238–249
Injection: 4: 387–397
Injection molding: 6: 531–545
Instantaneous measurement: 1: 48–65
Internal structure: 2: 107–119
Interstitial gas: 1: 90–106

Jet: 1: 28–47; 5: 493–505

Laminar flow: 2: 171–183
Laminarization: 2: 154–170
Laser: 8: 796–811
Latent heat: 8: 763–779
Latent heat of phase transformation: 3: 294–304
Length scales of turbulence: 1: 1–13
Liquid ice: 3: 250–268

Magnetic fluid: 7: 643–660
Marangoni effect: 4: 355–371
Mass transfer: 1: 14–27; 1: 28–47
Measurement: 5: 506–517
Melting heat transfer: 3: 250–268
Metal mold: 6: 531–545
Molecular dynamics: 5: 518–530
Monte Carlo method: 6: 559–572
Moving coordinates system: 5: 531–545
Multilayer insulation: 8: 747–762
Multiphase flow: 5: 447–461; 5: 493–505; 6: 611–624; 7: 661–671

Narrow surface: **6**: 546–558
Natural convection: **2**: 139–153; **3**: 213–223; **3**: 250–268; **4**: 387–397; **5**: 462–479; **6**: 546–558; **6**: 596–610; **7**: 672–689; **8**: 838–848
Nonequilibrium: **5**: 518–530
Nongray media: **6**: 559–572
Nonhomogeneous porous layer: **6**: 573–594
Numerical analysis: **4**: 398–415; **4**: 416–434; **5**: 462–479; **5**: 493–505; **6**: 559–572; **7**: 672–689
Numerical prediction: **4**: 325–339
Numerical simulation: **6**: 596–610
Nusselt number: **2**: 198–212; **6**: 596–610

Optimal thermal design: **8**: 838–848
Optimum fin geometry: **4**: 372–386

Parallel-plate channel: **2**: 171–183
Particles: **5**: 493–505
Performance evaluation: **2**: 184–197
Phase change: **1**: 66–77; **7**: 731–746
Pipe fabricated from insulating material: **3**: 305–324
Pipe flow: **3**: 213–223; **5**: 480–492
Piping heat loss: **3**: 305–324
Pitch ratio: **8**: 796–811
Plasma spraying: **5**: 493–505
Porosity: **8**: 780–795
Porous media: **2**: 139–153; **3**: 224–237; **4**: 398–415
Pressure distribution: **8**: 796–811
Pressure drop: **3**: 238–249; **6**: 625–641
Pulsation: **5**: 480–492

Quenching: **3**: 281–293; **3**: 294–304

Reactor: **2**: 107–119
Reattachment: **7**: 716–730; **8**: 796–811
Refrigerant: **4**: 372–386
Reynolds stress turbulence model: **2**: 154–170
Rib: **8**: 796–811
Rod bundle: **2**: 198–212
Row of cylinders: **7**: 690–702

Secondary flow: **5**: 462–479
Sensible heat: **8**: 763–779
Separated flow steps: **7**: 716–730
Shear flow: **5**: 506–517
Silicon single crystals: **4**: 416–434
Similarity curve: **8**: 763–779
Similarity rule: **8**: 763–779
Single sphere: **8**: 838–848
Solidification: **4**: 398–415; **8**: 763–779
Spherical lighting fixture: **8**: 838–848
Spherical-particle layer: **6**: 573–594
Square array: **2**: 198–212
Square cavity: **2**: 139–153; **7**: 672–689
Staggered baffle: **2**: 171–183
Statistics: **1**: 48–65
Steam absorption: **4**: 355–371
Stefan number: **8**: 763–779
Straight fin: **8**: 763–779
Subcooling: **8**: 812–827
Suction: **4**: 387–397
Surface-worked heat-transfer tube: **7**: 703–715

Temperature boundary layer: **6**: 573–594
Temperature of phase transformation: **3**: 294–304
Thermal conductivity: **5**: 435–446
Thermal conductor: **1**: 78–89; **1**: 90–106
Thermal diffusivity: **5**: 480–492; **8**: 780–795
Thermal engineering: **7**: 731–746
Thermal history: **4**: 416–434
Thermal insulation: **8**: 747–762
Thermal performance: **8**: 763–779
Thermal radiation: **3**: 224–237; **4**: 416–434; **5**: 518–530; **6**: 559–572; **8**: 747–762
Thermally insulated piping: **3**: 305–324
Thermoelectrically conducting fluids: **7**: 672–689
Thermosiphon: **6**: 611–624; **8**: 812–827
Thin plate: **3**: 281–293
Tinplate: **3**: 281–293
Transformer: **6**: 625–641
Transitional Reynolds number: **2**: 198–212
Triangular array: **2**: 198–212
Turbulence: **1**: 14–27; **2**: 107–119; **3**: 213–223; **8**: 796–811
Turbulence promoter: **2**: 184–197

Turbulent boundary layer: **1**: 1–13
Turbulent flow: **3**: 238–249; **4**: 325–339; **4**: 387–397; **8**: 796–811
Turbulent heat flux equation: **2**: 120–138
Turbulent mixing: **1**: 28–47; **1**: 48–65
Two concentric spheres: **8**: 838–848
Two-equation model: **3**: 213–223; **4**: 325–339
Two-phase: **8**: 812–827

Ultrasonic: **6**: 546–558
Ultrasonic velocity: **8**: 780–795
Upward-facing surface: **1**: 66–77

Velocity: **1**: 48–65
Velocity distribution: **1**: 28–47; **8**: 796–811
Velocity measurement: **1**: 14–27
Vertical enclosure: **6**: 596–610
Vertical flat plate: **4**: 387–397
Vibrating cylinder: **5**: 462–479
Viscous heat generation: **6**: 531–545
Visualization: **2**: 184–197
Vortex: **5**: 506–517

Wake: **7**: 690–702
Water cooling: **6**: 546–558
Winding: **6**: 625–641

Yaw angle: **8**: 828–837
Yawed cylinder: **8**: 828–837